



## Synthetic Multi-Purpose Grease

AMSOIL Synthetic Multi-Purpose Grease effectively reduces friction and wear, providing peace-of-mind that components are running clean and trouble-free for outstanding performance, long life and reduced maintenance and downtime, even in severe operating conditions. Qualified against the highest grease standards and designed for multiple-use applications, Synthetic Multi-Purpose Grease provides the ultimate in protection and convenience.

### Performance Features

Composed of premium-quality synthetic base oils and calcium sulfonate complex thickeners, Multi-Purpose Grease provides exceptional film strength and shear resistance for premium component protection in severe service, while also providing superior adhesion properties to effectively resist water washout and stay in place longer. It excels in temperature extremes by providing excellent oxidation stability, high-temperature dropping point and low-temperature torque value and pumping capability. AMSOIL Synthetic Multi-Purpose Grease is formulated with oil soluble extreme-pressure additives for heavy loads, as well as oxidation and corrosion inhibitors to protect against the effects of rust and corrosion.

- **Resists** thermal and oxidation degradation
- **Excellent** water-washout resistance
- **Outstanding** low-temperature pumpability and torque value
- **Adhesive** and shear stable to prevent squeeze out
- **Excellent** load-carrying and EP performance

### Application Recommendation

AMSOIL Synthetic Multi-Purpose Grease is the preferred choice for a wide range of ambient temperatures, wet environments, wheel bearings, suspension systems and other automotive applications.

AMSOIL Synthetic Multi-Purpose Grease is recommended in heavy- and light-duty applications found in manufacturing facilities, automobiles, trailers and landscaping, agricultural and powersports equipment. These include, but are not limited to, roller bearings, plain bearings, thrust bearings, gears, electric motors, presses, winches, bushings, wheel bearings, chassis lubrication, universal joints, ball joints, tie-rod ends and steering knuckles.



**NLGI #2**



## TYPICAL TECHNICAL PROPERTIES

### Synthetic Multi-Purpose Grease (GLC)

|   | GLC                       | NLGI GC-LB Requirements |
|---|---------------------------|-------------------------|
| Thickener                                     | calcium sulfonate complex | NR*                     |
| NLGI Consistency Grade                        | 2                         | NR*                     |
| NLGI Performance Grade                        | GC-LB                     | NR*                     |
| Operating Range °F (°C)                       | -40 to 350 (-40 to 177)   | NR*                     |
| Penetration (ASTM D217) (25°C [77°F], 0.1 mm) |                           |                         |
| worked 60 strokes                             | 282                       | 220-340 min             |
| Dropping Point °F (°C) (ASTM D2265)           | >540 (>282)               | 428 (220) min           |
| High-Temperature Life, hours (ASTM D3527)     | 120                       | 80 min                  |
| Water Washout, % (ASTM D1264)                 | 1.70                      | 15 max                  |
| Rust and Corrosion (ASTM D1743)               | Pass                      | Pass                    |
| Oil Separation, % loss (ASTM D1742)           |                           |                         |
| (24 hours, 25°C [77°F])                       | 0                         | 6.0 max                 |
| Leakage, g lost (ASTM D4290)                  | 4.2                       | 10 max                  |
| Four-Ball Wear Test, mm scar (ASTM D2266)     | 0.40                      | 0.60 max                |
| Fretting Wear, mg (ASTM D4170)                | 2.3                       | 10 max                  |
| Four-Ball EP, kgf (ASTM D2596)                |                           |                         |
| Weld Point                                    | 620                       | 200 min                 |
| Load Wear Index                               | 74                        | 30 min                  |
| Timken OK Load Test, lbs (ASTM D2509)         | 70                        | NR*                     |
| Low-Temperature Torque, N•m (ASTM D4693)      |                           |                         |
| (-40°C [-40°F])                               | 6.4                       | 15.5 max                |
| Oil viscosity                                 |                           |                         |
| 40°C (104°F), cSt                             | 165                       | NR*                     |
| Color   | Red                       | NR*                     |
| Texture                                       | Smooth with tack          | NR*                     |

NR: not required for NLGI GC-LB labeling

## APPLICATION MAINTENANCE

Maintaining a clean work environment is important when equipment greasing is performed. Wipe grease fittings clean prior to injecting grease to prevent contaminant ingestion. Maintain bearing housings one-third to one-half full of grease. Do not over-grease, as excessive heat buildup can result. Supplement standard grease maintenance by periodically cleaning and packing housings with fresh grease on an established maintenance schedule.

## AMSOIL PRODUCT AVAILABILITY

AMSOIL Synthetic Multi-Purpose Grease is available in 3-oz. cartridges, 14-oz. cartridges, 35-lb. lugs, 120-lb. kegs, 400-lb. drums and in a 3 oz. cartridge grease gun kit.

## COMPATIBILITY

AMSOIL Synthetic Multi-Purpose Grease is compatible with many other types of greases. However, it is recommended that

when changing greases, the equipment be cleaned of the old grease when possible or flushed with a liberal amount of Multi-Purpose Grease while the mechanism is in operation. Closely monitor the system for any inconsistencies. Grease compatibility questions should be referred to your AMSOIL representative or AMSOIL INC.

## AMSOIL PRODUCT WARRANTY

AMSOIL products are backed by a Limited Liability Warranty. For complete information visit [www.amsoil.com/warranty.aspx](http://www.amsoil.com/warranty.aspx).

## HEALTH & SAFETY

This product is not expected to cause health concerns when used for the intended application and according to the recommendations in the Safety Data Sheet (SDS). An SDS is available via the Internet at [www.amsoil.com](http://www.amsoil.com) or upon request at (715) 392-7101. **Keep Out of Reach of Children.**



AMSOIL products and Dealership information are available from your local full-service AMSOIL Dealer.